


Reimagine Your Edge



## 4244XS-EL XGS-PON/10GS Outdoor ONT

1G/10G optimized hardened electronics with multiple data and voice FXS ports for outdoor and indoor installations using Zhone leading-edge technology.

### Features & Benefits

- + Supports 1Gbps and 10Gbps (Downstream/Upstream) with pluggable SFP+ WAN interface
- + Four gigabit multi-rate 10/100/1000Base-T Ethernet interfaces
- + Four POTS interfaces compliant to SIP and MGPC telephony standards
- + Supported within Corning fiber transition housing with integrated fiber management

The Zhone 4226XS-EL is the next generation of 10Gbit Optical Network Terminal (ONT), able to support service provider requirements for high-speed data and voice for outdoor enclosure and indoor structured wiring applications. The SFP+ based uplink supports both symmetric 1 and 10 XGSPON and 1G and 10G Active Ethernet technologies by simply swapping the optical transceiver.

All Ethernet LAN ports can be used to support any-port-any-service model or separated into different services, allowing the configuration of dedicated ports for IP video and data. Unique VLANs may also be configured per user to ensure full isolation of each customer's data traffic. With unique Zhone's software management features, subscribers can enjoy hyperconnected multimedia services much easier, faster, and more reliable than ever before.

The Zhone 4226XS-EL includes one SFP+ WAN interface, four 10/100/1000Base-T ports, and four FXS RJ11 voice ports for phone or fax. The ONT supports wire-speed L2 bridging and L3 gateway features, with carrier grade voice services and option for Zhone approved battery backup unit with battery status telemetry.

## Service Scenario

The XGS-PON/10GS network consists of a 1G and 10G+ Optical Line Termination (OLT) located in a central location, and a set residential Single-Family Unit (SFU) and Multi Dwelling Unit (MDU) locations with Optical Network Terminals (ONTs). Between them is the optical distribution network (ODN) comprised of fibers, passive optical splitters, and couplers.

The 4244XS-EL ONT supports 10G capable downlinks using the XGS-PON or 10G Ethernet standard. Services include High-Speed Internet (HIS), Packet Voice, IPTV, OTT video, and cloud enabled services to multi-media devices.

## Key Service Attributes

- + XGS-PON ITU-T G.9807.1-compliant interface or 1G and 10G point-to-point Ethernet interface
- + Supports 10Gbps 1270nm burst-mode transmitter and 1577nm continues-mode receiver
- + Four 10/100/1000MBase-T Ethernet ports (RJ45) supporting 1Gbps symmetrical services
- + Four voice ports, FXS interfaces compliant to ANSI or ETSI standards, SIP and MGCP
- + IPTV multicast, IGMPv2 and IGMPv3 services
- + Any-port, Any-service data model
- + Traffic management including Q-in-Q tagging, 802.1Q VLANs, multiple subscriber VLANs, per-port rate limiting
- + 802.1p priority bits, DiffServ and priority queuing based on service types.
- + OMCI and TR-069/TR-98 management
- + Zhone Universal Service Provisioning (USP), ONT SNMP Client
- + Local Web UI, Zhone CPE Manager feature set
- + +12 VDC power source, option for battery backup

## 4244XS-EL Industrial Temp Outdoor ONT

### Product Specifications

#### Hardware

- Electronic Dimensions  
Width: 7.9" (200mm)  
Depth: 1.2" (30.5mm)  
Height: 9.0" (229mm)
- Electronics Weight .9 LB (0.4 kg)
- Enclosure Dimensions  
Width: 9.9" (251mm)  
Depth: 3.8" (97mm)  
Height: 12.7" (322mm)
- Enclosure Weight 3.5 LB (1.6 kg)
- 256MByte Flash Memory
- 512MByte SDRAM (DDR3)
- SFP+ cage WAN Interface
- Capacity: 10 Gbps Down/10 Gbps Up

#### Interfaces

- WAN: 1 SFP+ cage, xPON or Ethernet
- LAN: 4 ports 10/100/1000MBase-T Ethernet (RJ45) and 1 port 10GBase-T (RJ45 or Base-LR/LW (SFP))
- Telephone: 4 ports 2-wire RJ11
- Power: 1 7-pin screw-terminal connector
- LED Indicators
- Recessed RESET button

#### XGS-PON/10GS

- 1 x10 MSA-compliant SFP+ cage for PON or AE modules (optical transceiver not included)
- XGSPON req: ITU-T G.9807.1-compliant module. 10Gbps 1270nm burst-mode transmitter and 1577nm continues-mode receiver.
- 1G and 10G AE req: IEEE 802.3ae 10GBaseLR/LW compliant module.
- Forward Error Correction (FEC) per G.989.3
- Dying Gasp

#### Ethernet LAN ports

- Auto-MDI-X crossover control
- Auto-Speed or manual selection
- IEEE 802.3ab 1000Base-T
- IEEE 802.3u 100Base-T
- IEEE 802.3az EEE
- IEEE 802.1x Authentication
- IEEE 802.3az EEE
- IEEE 802.1x Authentication

# 4244XS-EL Industrial Temp Outdoor ONT

## Product Specifications

### Telephone

- SIP (RFC 3261)
- MGCP
- Codec: G.711 (u-law and A-law), G.729B, G726
- RENs per line: 5 maximum
- Drop length: Residential short loop, 152.4m (500 ft.)
- Output max: 25mA
- Ring voltage: 48Vrms @ 20/25 Hz

### Quality of Service

- HW-based internal IEEE 802.1p (CoS)
- Strict Priority (SP)
- 802.1Q(VLAN tag) QoS mapping ToS/CoS
- 8 queues per port
- Classified traffic can be tagged with VLAN ID and Ethernet Priority bit, and can be assigned to priority queues
- Classify packets into different IEEE 802.1p priority queues according to DSCP values (RFC 2475)
- The range of traffic shaping or rate-limit shall be between 64 Kbps to the maximum port rate with 64kbps granularity. The accuracy error shall be less than ±10%
- DSCP IP CoS (RFC 2475)

### Software Features

- IEEE802.1D and IEEE802.1Q
- Address learning with auto aging-L2/BPDU Filter
- Support 2048 MAC learning addresses
- Multiple T-CONTs/GEM ports per device
- Flexible mapping between GEM port and T-CONT
- Priority queues and scheduling on upstream
- Activation with automatic discovered serial Number and password

### IP Routing and Firewall

- DHCP, Static-IP and PPPoE
- NAT/NAPT
- DNS Proxy
- DHCP Server
- UPnP, plug and play

### IPv6

- IPv4 and IPv6 Dual-Stack-Lite
- Bridged Mode (transparent pass thru of IPv6 frames)
- IPv6 support of BRouted and PPPoE Bridged VLANs
- DHCPv6 client and server
- Router Advertisement on LAN-side interfaces
- SLAAC for automatic acquisition of WAN-side IPv6 addresses and GW
- CLI, HTTP and TR-069 management via IPv6

### Environmental

- Enclosure IP45 Rating
- Operating Temperature -40~149°F (-40~+65°C) Industrial Temperature
- Storage temperature -40~185°F (-40~85°C)
- Operating humidity 10 to 95% (noncondensing)
- Altitude: -200 to 10,000 feet (-61 to 3,048 m) above sea level

### Powering

- DC power, +12 VDC nominal, +10-16 VDC / s1.0A
- Input power, 90-240VAC, 50/60Hz
- Power consumption, ~12W maximum

### Management

- ITU-T 984.1/G988 compliant OMCI interface
- CPE Manager Web UI
- CLI over telnet
- SNMP Client
- TR-069, TR-104, TR-98
- Zhone Universal Service Provisioning
- LED indications for status

### Compliance

- FCC Part 15 Class B
- ICES-003 Class B
- EN55022, EN55024
- IEC 62368-1
- FDA IEC 60825-1
- RoHS 2015/863/EU

## Ordering Information

Model	Description
<b>4244XS-EL</b>	1 x SFP+ cage, xPON and 10GS Ethernet 4x 1G RJ45 ports 4x POTS RJ11 ports 1x 7-pin screw-terminal connector
<b>HX-4244XS-EL</b>	ONT electronics, no power supply
<b>ZNID-ENCL-422X</b>	422x fiber termination enclosure. (ONT electronics sold separately.)
<b>XCVR-XGS-SFP+-ONU-IA</b>	XGS PON 10/10G ONU SFP+, 1270NM TX, 1577NM RX SINGLE FIBER SC/APC
<b>XCVR-AE-SFP+-SBD-1270-20KM-IA</b>	ACTIVE ETHERNET 10GB/S SFP+, 1270NM TX, 1330NM RX, 20KM, SINGLE FIBER, LC/UPC



42xx Fiber Termination Enclosure



Zhone Technologies, Inc