

SMART INSTALLATION TOOL

CTL-2000



NetComm have considered installation issues in its product strategy and specifically designed a smart and robust assistant to provide an easy, quick and accurate outdoor installation experience.

EFFICIENT SITE SURVEY

With a compact form factor, both easy to use and carry, the **CTL-2000 Smart Installation Tool** connects directly to the outdoor CPE. Attached through the RJ45 Power Over Ethernet port on the outdoor CPE, it delivers power via its replaceable rechargeable battery, providing the requisite portability for an efficient site survey.

The **Smart Installation Tool** is compatible with all of NetComm's Outdoor CPE, irrespective of form factor, power levels and frequency bands.



HIGH INSTALLATION PRECISION

The **CTL-2000** includes an integrated electronic compass allowing capture of device bearing and elevation to an accuracy of 10 degrees.

CTL-2000 integrates a WiFi 802.11b/g/n access point operating on the 2.4GHz band to connect to a visual and practical web interface. The web interface displays on portable wireless devices such as smartphones or laptops and provides clear diagnostic and troubleshooting information.

This allows a straightforward, reliable and interactive configuration of the outdoor CPE, easily finding the best location at the premises.



KEY FEATURES CONT.



SMART & ROBUST DESIGN

The robust weather resistant design is suitable for outdoor usage and has been designed to accommodate standard health and safety practices for working on ladders and roofs as well as the practical processes associated with the survey and installation of Outdoor CPE.



REMOVEABLE & RECHARGEABLE BATTERIES

The tool comes complete with two rechargeable batteries and an AC battery charger.

The batteries supplied are of a common format compatible with power tools from manufacturers such as Milwaukee. Replacement batteries or higher power batteries can be easily obtained via local or online resellers.

DEVICE FEATURES



SUPPORTING AURORAPRO INSTALLATION SMARTPHONE APPLICATION

The tool can be used together with **NetComm's AuroraPRO** Technician Smartphone Installation Application during Site Survey and Installation.

Alternatively the **CTL-2000** can be used on its own, and its integrated signal level LEDs used to establish correct outdoor CPE placement and orientation.



HANDS FREE OPERATION

When connected to an outdoor CPE the **CTL-2000** can optionally be mounted onto a mounting rail that is integrated onto NetComm's outdoor CPE enclosures.

When using the tool with an outdoor CPE without such a mounting rail, the provided carabiner strap may be used to hang the tool from an appropriate anchoring position on the outdoor CPE or Mounting Bracket.

Once mounted or hung on/from an outdoor CPE, the installers hands are free to be used for other activities.



RJ45 CONNECTION TO OUTDOOR UNIT


The **CTL-2000** provides power to an outdoor CPE via Power Over Ethernet, and is rated up to 30W.

The tool comes with a 50cm Cable with weather proof RJ45 glands on each end. If the cable is damaged, the installer is able to replace the cable and re-use the RJ45 glands.


The installation of the glands on the cable is identical to the practice followed by the Installer on the final installed Ethernet cabling to the outdoor CPE.

When not in use, the provided cable can be secured using an attached cable tidy.

WHAT'S IN THE BOX




1 x Installation Assistant
(CTL-2000)




2 x Battery Packs
(Li-ion, 2Ah, removable)




1 x AC Battery Charger



1 x Ethernet
Passthrough Adaptor



AC Charging Cables:
NA, EU, AU, UK



1 x Storage Pouch



1 x Carabiner Strap



1 x Safety/Compliance Leaflet
1x Welcome Card



TECHNICAL SPECIFICATIONS

MODEL NUMBER

- › CTL-2000

CONNECTIVITY

- › Integrated WiFi 802.11b/g/n 2.4 GHz
- › 1x Power Over Ethernet Connection RJ45
- › Bluetooth Low Power

POWER OVER ETHERNET

- › 802.3at 30W Power Class

ON BOARD STORAGE

- › 8GB eMMC - To be used for storage of outdoor CPE firmware images and configuration files

SUPPLIED BATTERIES

- › 2 x 2Ah Rechargeable Lithium-Ion Batteries (12 V)
- › >2 hours battery life on a single fully charged battery @15W

BATTERY CHARGER

- › AC Powered single battery charger provided.
- › Input: 100-240 VAC
- › Output: 12V/3A DC

REPLACEMENT BATTERIES

- › Compatible with 48-11-2430 and 48-11-2460 batteries available from local online resellers
- › Warranty is only applicable whilst using the NetComm supplied batteries or certified* branded replacement batteries. The use of generic compatible batteries from other vendors is at the users risk.

LED INDICATORS

- › 7 Multi Functional LEDs
 - › 1 x Power/Battery
 - › 1 x Compass Calibration
 - › 1 x Radio Access Technology (4G/5G)
 - › 3 x Radio Access Signal Level
 - › 1 x Information

DIMENSIONS & WEIGHT

Dimensions

- › 198 mm (7.8 in) with battery inserted (L)
- › 77 mm (3 in) (W)
- › 91 mm (3.6 in) (H)

Weight

- › 527g (1.15 lb) Ethernet cable, without battery
- › 712g (1.6 lb) Including Ethernet cable, with 2Ah battery

ENVIRONMENTAL

- › Ruggedized design suitable for outdoor usage
- › Operating temperature -15° to +40°C

CERTIFICATION & COMPLIANCE

- › FCC
- › UL
- › ROHS
- › RCM
- › CE
- › IC

* 48-11-2430 and 48-11-2460 batteries

NetComm CTL-2000 Spec Sheet Rev 5

Trademarks and registered trademarks are the property of NetComm Wireless Pty Ltd or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the actual product.



NETCOMM
HEAD OFFICE | SYDNEY
18-20 Orion Road Lane Cove NSW 2066
Sydney | Australia | +61 2 9424 2070
www.netcomm.com



ZHONE
HEAD OFFICE | USA
5700 Tennyson Pkwy
Suite 400, Plano, TX 75024
Texas | USA | +1 877-946-6320
www.zhone.com



NetComm
a division of **zhone**