



DP010011



1-Port Gfast

Distribution Point Unit (DPU)

Designed to assist operators in maximizing revenue from a **Fiber-to-the-Home (FTTH)** deployment, particularly in scenarios where deploying the final fiber segment is difficult, expensive or impractical. The DZS **DP010011 1-Port Gfast DPU** acts as a fiber extender, delivering gigabit-class service over the existing copper lead-in cable.



High Speed Broadband

Gfast 212MHz provides aggregate speeds up to 2Gbps, enabling the delivery of fiber-equivalent gigabit services over legacy copper.



Reverse Power

The DPUs are reverse powered by the **Network Termination Device (NTD)** installed in the end-user premises, avoiding the cost and delay associated with providing a local AC power connection and eliminating potentially difficult negotiations with apartment owners over access to, and charges for, AC power.



Advanced Remote Management

The DPUs support Netconf/YANG, offering full remote device management and troubleshooting by using a Persistent Management Agent Aggregator (PMAA).



Anywhere Installation

Silent, energy-efficient passive cooling design withstands a wide temperature range from -20°C to +70°C. Fully sealed waterproof outdoor housing with surge protection provides enhanced reliability even in the toughest conditions.



DP010011 1-Port Gfast DPU

Technical Specifications

Connectivity

- + 1 x GPON (ITU G.984) port
- + 1 x Gfast (ITU G.993.2/G.9701) port

Supported Standards

- + IEEE 802.1Q VLANs
- + IEEE 802.1Q Class of Service ("802.1p")
- + IEEE 802.1ad (Stacked VLANs)
- + IEEE 802.1ag
- + ITU Y.1731 (Fault Management and Performance Monitoring)
- + ITU G.993.2
- + ITU G.984 GPON
- + ITU G.988 OMCI
- + ITU G.9700 & G.9701 (G.fast)
- + Broadband Forum TR-156/TR-247/TR-255
- + Broadband Forum TR-301/TR-355 (DPU Management)

Regulatory Compliance

- + CE
- + FCC
- + RoHS
- + WEEE

Safety Standards

- + IEC/EN 62368-1 Audio/video, information and communication technology equipment - Part 1: Safety requirements

EMC standards

- + EN 55032, Class B
- + EN 55035

Power Supply

- + Powered by NDD-03xx Gfast NTD
- + **Output:** DC 60V/250mA max

Dimensions & Weight

- + 248mm (L) x 150mm (W) x 56mm (H) (incl. mounting flanges)
- + 1.1 kg approx.

Environmental Performance

- + **Operating temperature range:** -20°C to +70°C
- + IP68 rated housing
- + Passively cooled
- + Maintenance free design

Deployment Scenarios:

Where FTTH deployment is blocked to a single home

Key Features

- + Gfast 212a profile
- + Full support for ITU G.9701 G.fast specification including Amendments 1, 2 & 3
- + Robust - designed for indoor and outdoor wall-mount installations
- + Reverse powered (SR2)
- + Passive cooling design with a wide temperature range of -20°C to +70°C
- + IP68 rated, industrial grade product
- + K.45 surge protection
- + Clean appearance and discrete cable management suit deployment in public spaces (e.g. building hallways)
- + Installation tool and accessories enable easy, quick and reliable installation
- + Magnetic button on front panel allows technicians to re-activate LEDs, reboot DPU or restore factory default settings with a magnet wand
- + 1 x GPON (ITU G.984) port
- + 1 x Gfast (ITU G.993.2/G.9701) port

DZS DP010011 1-port Gfast DPU Data Sheet Rev 2

Specifications are subject to change without notice. Images shown may vary slightly from the actual product.
© 2025 | All Rights Reserved



Contact DZS today

Website:
www.DZSi.com
www.DZSi.com/contact-us

Email:
info@DZSi.com
support@DZSi.com