

8-PORT GFAST 10G DISTRIBUTION POINT UNIT (DPU)

DP080021



Designed to assist operators in maximizing revenue from a **Fiber-to-the-Home (FTTH)** deployment, particularly in scenarios where deploying the final fiber segment is difficult, expensive or impractical. The NetComm **DP080021 8-Port Gfast 10G DPU** acts as a fiber extender for **XGS-PON** networks, delivering gigabit-class service over the existing copper lead-in cable.



HIGH SPEED BROADBAND

Gfast 212MHz provides aggregate speeds up to 2Gbps, enabling the delivery of fiber-equivalent gigabit services over legacy copper.



REVERSE POWER

The DPUs are reverse powered by the **Network Termination Device (NTD)** installed in the end-user premises, avoiding the cost and delay associated with providing a local AC power connection and eliminating potentially difficult negotiations with apartment owners over access to, and charges for, AC power.



ADVANCED REMOTE MANAGEMENT

The DPUs support Netconf/YANG, offering full remote device management and troubleshooting by using a Persistent Management Agent Aggregator (PMAA).



ANYWHERE INSTALLATION

Silent, energy-efficient passive cooling design withstands a wide temperature range from -20°C to +65°C. Fully sealed waterproof outdoor housing with surge protection provides enhanced reliability even in the toughest conditions.

TECHNICAL SPECIFICATIONS

CONNECTIVITY

- › 1 x XGS-PON (ITU G.9807.1) port with fiber lead
- › 8 x Gfast (G.9701) ports with 1-pair copper lead

SUPPORTED STANDARDS

- › IEEE 802.1Q VLANs
- › IEEE 802.1Q Class of Service ("802.1p")
- › IEEE 802.1ad (Stacked VLANs)
- › IEEE 802.1ag
- › ITU Y.1731 (Fault Management and Performance Monitoring)
- › ITU G.993.2
- › ITU G.9807 .1
- › ITU G.988 OMCI
- › ITU G.9700 & G.9701 (G.fast)
- › Broadband Forum TR-156/TR-247/TR-255
- › Broadband Forum TR-301/TR-355 (DPU Management)

POWER SUPPLY

- › **Input:** 60V/42W
- › Powered by NDD-03XX Gfast NTD
- › **Output:** 60V/250mA max

SAFETY STANDARDS

- › IEC/EN 62368-1 Audio/video, information and communication technology equipment - Part 1: Safety requirements

EMC STANDARDS

- › EN 55032, Class B
- › EN 55035

REGULATORY COMPLIANCE

- › CE
- › FCC
- › RoHS
- › WEEE

DIMENSIONS & WEIGHT

- › 350mm (L) x 300mm (W) x 91mm (D)
- › 6.6kg approx.

ENVIRONMENTAL PERFORMANCE

- › **Operating temperature range:** -20°C to +65°C
- › IP68 rated housing
- › Passively cooled
- › Maintenance free design

DEPLOYMENT SCENARIOS

Indoors, outdoors, on walls, in pits or on poles.

KEY FEATURES

- › Gfast 212a profile
- › Full support for ITU G.9701 G.fast specification including Amendments 1, 2 & 3
- › Robust - designed for underground-pit, pole mount and wall-mount installations
- › Passive cooling design with a wide temperature range of -20°C to +65°C
- › K.45 surge protection
- › IP68 rated, industrial grade product that can be installed underground
- › Installation tool and accessories enable easy, quick and reliable installation
- › Magnetic button on front panel allows technicians to re-activate LEDs, reboot DPU or restore factory default settings with a magnetic wand
- › 1 x XGS-PON (ITU G.9807.1) port - outdoor-rated fiber lead with hardened connector
- › 8 x Gfast (G.9701) ports with outdoor-rated copper lead

NetComm DP080021 8-port Gfast 10G DPU Spec Sheet Rev 11

Trademarks and registered trademarks are the property of NetComm Wireless Pty Ltd or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the actual product.



NETCOMM
HEAD OFFICE | SYDNEY
18-20 Orion Road Lane Cove NSW 2066
Sydney | Australia | +61 2 9424 2070
www.netcomm.com



ZHONE
HEAD OFFICE | USA
5700 Tennyson Pkwy
Suite 400, Plano, TX 75024
Texas | USA | +1 877-946-6320
www.zhone.com



NetComm
a division of zhone